

# Dejero

# WayPoint 50

One-output compact receiver



The WayPoint 50 receiver reconstructs broadcast-quality video transported over multiple IP connections from a Dejero transmitter, decodes HEVC or AVC, and outputs to SDI or MPEG-TS workflows.

WayPoint 50 receivers fit in short-depth 19" rack systems, making them a great choice for production vehicles where space is a premium. They are also designed to fit in portable

fly away kits to provide receiving capability on location. And if you just need a single output at your facility, this is the receiver model to choose.



## COMPACT DESIGN

The short-depth chassis is perfect for racking in vehicles and portable fly away kits where space is a premium.




## BROAD COMPATIBILITY

Receive and reconstruct broadcast-quality HEVC and AVC streams from all Dejero transmitters.



## IFB SUPPORT

Communicate with camera operators and talent in the field while in live and stand-by mode.



## MANAGE ANYWHERE

Manage all your receivers and output assignments remotely from any device with a web browser.

# PRODUCT SPECIFICATIONS

## KEY FUNCTIONS

<b>RECONSTRUCTS</b>	Broadcast-quality video transported over multiple IP connections
<b>DECODES</b>	HEVC or AVC
<b>OUTPUTS</b>	To SDI or MPEG-TS IP workflows

## 3G-SDI OUTPUT

<b>VIDEO</b>	Formats: 1080p 23.98/25/30/50/59.94/60, 1080i 25/29.97/30, 720p 50/59.94/60, 576i 25, 480i 29.97
<b>AUDIO</b>	2-, 4-, or 8-channel for live transmission Note: Transmitters sending recorded clips will send 2- or 4-channels of audio

## MPEG-TS OUTPUT

<b>VIDEO</b>	Formats: 1080p 23.98/25/30, 1080i 25/29.97/30, 720p 50/59.94/60, 576i 25, 480i 29.97 Bitrate: Constant, up to 30 Mb/s Codec: MPEG-4
<b>AUDIO</b>	2- or 4-channel Bitrate: Constant, up to 320 Kbps for each channel pair Codec: AAC-LC
<b>TRANSPORT</b>	Protocols: UDP, RTP

## NETWORK CONNECTIONS

<b>ETHERNET</b>	2 x 1 Gb/s port for LAN/WAN
-----------------	-----------------------------

## POWER

<b>SUPPLY</b>	100-240 VAC 50/60 Hz AC
<b>CONSUMPTION</b>	Max. 100 W

## PHYSICAL

<b>DIMENSIONS (H x W x D)</b>	1U short-depth 19" rackmount, 4.4 x 42.7 x 24.9 cm (1.7 x 16.8 x 9.8 inches)
<b>WEIGHT</b>	4.2 kg (9.2 lbs)
<b>OPERATING TEMPERATURE</b>	-10 °C to 45 °C (14 °F to 113 °F)
<b>STORAGE</b>	35 hours of HD (6 Mb/s)
<b>INTERFACES</b>	GenLock (BNC), SDI out (BNC), 2 x RJ45 Ethernet, IFB (3.5 mm microphone connector), 1 x USB 2.0 (front), 4 x USB 3.0 (rear)



GENLOCK



SDI OUT



RJ45 ETHERNET



IFB

# ADDITIONAL FEATURES

## MULTIPLE OUTPUT FORMATS

Supports SDI or MPEG-TS over IP playout workflows

## CODEC AUTO-DETECTION

Automatically detects and decodes HEVC or AVC without human intervention

## HIGH PERFORMANCE

Intel processor designed for all day, every day reliability

## BLACK BURST AND TRI-SYNC

Genlock input accepts black burst or tri-sync reference signals for video synchronization

## MULTICHANNEL AUDIO

Supports 2, 4, or 8 different simultaneous audio outputs

## SOFTWARE UPDATES

New and enhanced features and compatibility with new devices is provided with software updates

Contact us to learn more about WayPoint 50

Full specifications available at [www.dejero.com/waypoint](http://www.dejero.com/waypoint)

# Dejero

[www.dejero.com](http://www.dejero.com)  
[connect@dejero.com](mailto:connect@dejero.com)  
+1 519 772 4824

Copyright © 2020 Dejero Labs Inc. Dejero is a trademark or registered trademark of Dejero Labs Inc. All other trademarks are the property of their respective owners. Design, features, and specifications are subject to change without notice. D-PB129-003 05/2020