

Dejero

CuePoint 50

Compact return feed server




The compact Dejero CuePoint 50 return feed server sends low-latency live program video and teleprompter feeds to on-air presenters, camera operators and other production personnel in the field to help them stay synchronized with central production during live broadcasts.

CuePoint 50 servers fit in short-depth 19" rack systems, making them a great choice for production vehicles where space

is a premium. They are also designed to fit in portable fly away kits to provide return feeds when on location.

250
milliseconds



SYNCHRONIZED PRODUCTION

Near real-time synchronization between on-air talent and broadcast facility helps avoid pauses and delays in live programs.

COMPACT DESIGN

The short-depth chassis is perfect for racking in vehicles and portable fly away kits where space is a premium.

EQUIPMENT SAVINGS

View return video and teleprompter feeds in the field on smartphones, tablets, and regular monitors.

MANAGE ANYWHERE

Manage all your return feed servers and feeds remotely from any device with a web browser.

PRODUCT SPECIFICATIONS

KEY FUNCTIONS

| | |
|--------------------------|--|
| RETURN VIDEO | Deliver live program video feed to remote location |
| TELEPROMPTER FEED | Deliver operator-controlled teleprompter feed to remote location for presenter to read a live script |

VIDEO

| | |
|-----------------------|---|
| INPUT FORMATS | 1080p 23.98/29.97/25/30/50/59.94/60, 1080i 25/29.97/30, 720p 50/59.94/60, 576i 25, 480i 29.97 |
| OUTPUT FORMATS | 720p, 540p, 360p |
| INPUTS | 2 x 3G/HD/SD-SDI |

NETWORK CONNECTIONS

| | |
|-----------------|-----------------------------|
| ETHERNET | 1 x 1 Gb/s port for LAN/WAN |
|-----------------|-----------------------------|

POWER

| | |
|--------------------|-------------------------|
| SUPPLY | 100-240 VAC 50/60 Hz AC |
| CONSUMPTION | Max. 100 W |

PHYSICAL

| | |
|-------------------------------|--|
| DIMENSIONS (H x W x D) | 1U short-depth 19" rackmount, 4.4 x 42.7 x 24.9 cm (1.7 x 16.8 x 9.8 inches) |
| WEIGHT | 4.2 kg (9.2 lbs) |
| OPERATING TEMPERATURE | -10 °C to 45 °C (14 °F to 113 °F) |
| INTERFACES | 2 x SDI in (BNC), 1 x RJ45 Ethernet |



SDI IN

RJ45 ETHERNET

ADDITIONAL FEATURES

MULTIPLE FEEDS

Supports up to 2 simultaneous source feeds from a single server and up to 8 feeds in the field

ADJUSTABLE RESOLUTION

Adjust the resolution received in the field to best suit needs and control costs

VIEWING VERSATILITY

View feeds on smartphones or tablets for wireless convenience while on location, or on any monitor displaying a browser window

PLATFORM AGNOSTIC

Additional Dejero equipment or apps not required

ENGO COMPATIBLE

Optionally receive feed on Dejero EnGo mobile transmitter and output to an external monitor

SOFTWARE UPDATES

New and enhanced features and compatibility with new devices is provided with software updates

Contact us to learn more about CuePoint 50

Full specifications available at www.dejero.com/cuepoint

Dejero

www.dejero.com
connect@dejero.com
+1 519 772 4824

Copyright © 2020 Dejero Labs Inc. Dejero is a trademark or registered trademark of Dejero Labs Inc. All other trademarks are the property of their respective owners. Design, features, and specifications are subject to change without notice. D-PB130-002 05/2020