

# SOL70BTX

## SOL07 Outside Broadcast Transmitter

### Overview:

A compact and feature-rich COFDM digital video transmitter, specifically designed for high quality wireless link applications. With proven Domo COFDM and H.264 encoder technology at its core enabling High Definition images the small size and ultra low power consumption give maximum operational performance. Designed to offer maximum flexibility, the unit has a variety of video input options including composite, 3G-SDI and HDMI plus true balanced audio.

The transmitter has an integrated control panel with sunlight-readable OLED display covering all major functions and has 16 user-defined presets. A wide range of swappable frequency bands are available from 200MHz to 8.9GHz. Integrated UHF band Camera Control is available as an option.

### Features and Benefits:

Ultra-low latency High Profile H.264 SD and HD encoding  
Video formats up to 1080p60 and optional 4:2:2 Chroma sampling

Industry standard DVB-T modulation for interoperability with existing systems

Domo Broadcast UML modulation for enhanced high frequency / high speed performance

Controlled via USB or RS-232, and integrated sunlight-readable OLED display

Designed for sports & events coverage, newsgathering and wireless studio camera applications

Integrated camera control option with wide range of supported manufactures

User swappable RF modules and battery plate options

Very low power consumption for extended field performance: typically 10.0W

Weighs between just 520g and 870g



### Product Information:

#### Product Includes:

CA0002	12V DC Power lead Lemo-wire 3m
CA0343	USB Control Cable
CA0579	XLR Audio Input Cable
SA3688	OBTX Support USB Stick

#### CCCAM Expansion Includes:

AP008822	1/4 Wave Antenna SMA 433MHz
----------	-----------------------------

#### CCCAM Expansion Requires:

OBTX-CCCAM-ENABLE	Enable Camera control RX upgrade
OBTX-CCCAM-xUP	At least one control Protocol and cable

# SOL70BTX

## SOL07 Outside Broadcast Transmitter

### Accessory Options (sold separately):

OBTX-V-OEM	Additional V-Mount battery plates
OBTX-AB-OEM	Additional Anton Bauer battery plates
OBTX-PAG-OEM	Additional PAG battery plates
OBTX-xxxxx-OEM	Additional RF module
OBTX-CCCAM-RMA	Factory fit Camera Control RX upgrade
OBTX-CCCAM-SUP	Sony Control protocol and cable
OBTX-CCCAM-PUP	Panasonic Control protocol and cable
OBTX-CCCAM-TUP	Grass Valley Control protocol and cable
OBTX-CCCAM-IUP	Ikegami Control protocol and cable
OBTX-CCCAM-HUP	Hitachi Control protocol and cable
OBTX-CCCAM-CAMPAC	Multiple Control protocol and cable bundle
CA3122	Composite Video Input Cable

### Related Documents:

100145	SOL07 User Guide
MW3286	OBTX RF Module Assembly Guide
MW3308	OBTX V-Mount Battery Plate Assembly Guide
MW3285	OBTX AB-Mount Battery Plate Assembly Guide
MW3309	OBTX PAG-Mount Battery Plate Assembly Guide

### Technical Specification:

#### IO

HDMI	HDMI Type A
SD/HD/3G-SDI	BNC
ASI Input	DIN 1.0/2.3
ASI Output	DIN 1.0/2.3
Composite / S-Video / RS232	7-way 0B Lemo
Balanced Stereo Audio	5-way 0B Lemo (CA0579 2x XLR3)
USB Control	6-way 0B Lemo (CA0343 Type-A USB)
External Power	4-way 0B Lemo (CA0002 2x Banana)
External PA	4-way 00 Lemo
Battery Pass-through	V/AB/PAG plates (optional)
RF Output	N-Type (100mW/50mW/10mW modes)

#### IO (with Camera Control)

Camera Interface	10-way Circular Hirose
Tally	5-way 0B Lemo
USB Upgrade	Micro-B USB
RF Input	SMA (403-473MHz)

### DVB-T Modulation

DVB-T Bandwidth	8MHz, 7MHz and 6MHz modes
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T Constellation	QPSK, 16QAM, 64QAM
DVB-T Guard Interval	1/4, 1/8, 1/16, 1/32
DVB-T Bitrates	3.732Mbps to 31.668Mbps

### Narrowband/UMVL Modulation

NB Bandwidth	2.5MHz, 1.25MHz and 625kHz modes
UMVL Bandwidth	8MHz, 7MHz and 6MHz modes
NB/UMVL FEC	1/3, 2/3
NB/UMVL Constellation	QPSK, 16QAM, BPSK, 8PSK
NB/UMVL Guard Interval	1/8, 1/16
NB Bitrates	144kbps to 4.879Mbps
UMVL Bitrates	1.317kbps to 14.869Mbps

### Camera Control Demodulation

CC Bandwidth	12.5kHz, 20kHz and 25kHz modes
CC Constellation	4PSK, GMSK
CC Sensitivity	-114dBm @ 25kHz Bandwidth -111dBm @ 12.5kHz Bandwidth

### Video

SD Input Format	PAL, NTSC (with or without pedestal) 720x576i 50Hz 720x480i 59Hz
HD Input Format	1920x1080i 60/59.94/50Hz 1920x1080p 30/29.97/25/24/23.97Hz 1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz
3G Input Format	1920x1080p 60/59.94/50Hz* (via 3G-SDI Level A/B or HDMI)
H.264 Compression	AVC / H.264 / MPEG-4 Part 10 High profile level 4.0 4:2:0 or 4:2:2 (optional)
ASP Compression	ASP / MPEG-4 Part 2 with NB modulation and SD only
Coding Options	Horizontal scaling of 3/4, 2/3, 1/2, 1/4 Vertical scaling of 1/2, 1/4 Sub-frame rate of 1/2, 1/4, 1/8, 1/24
Encoder Delay	1s to 10ms (mode dependant)
Encoder Bitrates	0.25Mbps to 32Mbps

# SOL70BTX

## SOL07 Outside Broadcast Transmitter

### Technical Specification (con't):

#### Audio

Analogue Audio Input	Balance analogue stereo pair +18dBu Max input level (up to 63dB gain)
Analogue Phantom Power	Off, 12V or 48V selectable
Digital Audio Input	SD/HD/3G-SDI 2 digital stereo pairs HDMI 1 digital stereo pair
Sample Rate	32kHz, 48kHz
Coding Modes	4 channels stereo or mono MPEG Audio Layer 1 64-448kbps MPEG Audio Layer 2 32-384kbps

#### Other

RS232 Data Input	1k2 to 115k2, 7/8 bit, no/odd/even parity
Remote Control	RS232 & USB Control from PC GUI Application or other device
Front Panel	Built in FCON field controller

#### Encryption

Type	ABS 32-bit as standard
Licensable	AES 128/256-bit (subject to export control)

#### Physical

Dimensions	L 170mm (142mm excluding connectors), W 97mm (94mm excluding connectors), H 35mm (without battery plates) or H 71mm (with V-lock or PAG plates) or H 62mm (with Anton Bauer plates)
Weight	520g to 870g depending on options

#### Power

DC Input	9.2V to 17.8V reverse polarity protected
Power Consumption	Typically 10.0W @ 100mW RF power with additional 2.0W for >6.0GHz Additional 0.5W for Camera Control

#### Environment

Temperature Range	-10 to +50 °C
Humidity	Less than 85% Non-Condensing

#### Frequency

100150	1.00-1.50GHz
198270	1.98-2.70GHz
300370	3.00-3.70GHz
440500	4.40-5.00GHz
550600	5.50-6.00GHz
640700	6.40-7.00GHz
700750	7.00-7.50GHz
810890	8.10-8.90GHz

#### Software License Code Includes

Silver (included)	DVB-T, Ultra Mobile Video Link (UMVL), MPEG-4 H.264 (SD)
Gold	Silver plus MPEG-4 H.264 (HD)
Platinum	Gold plus MPEG-4 H.264 (4:2:2)
Film Assist	Only Narrowband 2.5MHz, MPEG-4 H.264 (HD)

\* 3G-SDI Support subject to maximum encoder resolution limitations in initial software release of 960x1080p60/59.94 or 1280x1080p50

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email [solent.enquiries@domotactical.com](mailto:solent.enquiries@domotactical.com)

**DTC – Solent**  
Fusion 2, 1100 Parkway  
Solent Business Park  
Whiteley, Hampshire  
PO15 7AB, UK

T: +44 (0) 1489 566 750

**DTC – Tampa (Head Office)**  
3845 Gateway Centre Boulevard  
Suite 360  
Pinellas Park, FL  
33782, USA

T: +1 727 471 6900

**DTC – Randers**  
Haraldsvej 64B  
DK-8960  
Randers SØ  
Denmark

T: +45 8791 8100

**DTC – Singapore**  
21 Media Circle  
Infinite Studios #06-04  
Singapore  
138562

T: +65 6643 4700

**DTC – Brazil**  
Alameda Araguaia 2  
190 – Ed. CEA II – suite 1109  
Alphaville - Barueri  
São Paulo, Brazil  
06455-000

T: +55 11 2321 5055